

ELECTRO ACOUSTIC TRANSDUCER

BRT1209-05-50 Series




FEATURES:

- Small size and light for versatile usage
- High reliability and long life
- No electrical noise
- Low current consumption yet high sound pressure level
- Clear Sound and stabilized sound quality

USAGE:

- Alarm clocks, pagers, timers, etc.



**ALSO AVAILABLE IN FLYING LEAD WIRES 100M LENGTH

P/N BRT1209L-05-50

SPECIFICATIONS:

TYPE	BRT1209-05-50
RATED VOLTAGE (VDC)	5
OPERATING VOLTAGE (VDC)	1.5 ~ 5
*RATED CURRENT (mA)	Max. 50
COIL RESISTANCE (ohm)	50 ± 7.5
**COIL IMPEDANCE (ohm)	140
*SOUND OUTPUT AT 10cm (dB)	Min. 86
RESONANT FREQUENCY (Hz)	2,048
OPERATING TEMPERATURE (C)	- 20 ~ + 60
WEIGHT (g)	2

*Value applying rated voltage (2,048Hz, 1/2 duty, square wave)

**Value applying (2,048Hz, sine wave, measuring current 60uA)

Use ICC Intervox P/N BRT1209P-05-50 (for pin type) and BRT1209L-05-50 (for wire)

INTERVOX
International ©
 INTERNATIONAL COMPONENTS CORPORATION
 215 MCCORMICK DRIVE, BOHEMIA, NY 11716
 FAX: 631-952-9595 FAX: 631-952-9597

Title:

Electro Acoustic Transducer

Intervox Model #

BRT1209-05-50

Rev

A

Scale: mm

Date: 12/8/92

Sheet 1 of 1