



**International
Components
Corporation**

1337 Lincoln Avenue

Suite 5

Holbrook, NY 11741

Ph: (631) 952 - 9595 Fax:

E-mail: oemsales@icc107.com

ELECTRO-ACOUSTIC TRANSDUCER

[Contact Us](#)



Product: ELECTRO-ACOUSTIC TRANSDUCER

Description: Sealed For Flow Solder And Washing, Low Frequency

Part Number: BRT2513P-12-S

SPECIFICATIONS

CIRCUIT

Without Circuit

COIL IMPEDANCE

115 ohm

COIL RESISTANCE

120 \pm 15 ohm

FRAME DEPTH

12.5 mm

FRAME DIAMETER

24.7 mm

MAX CURRENT

55 mA

MOUNTING DIMENSIONS

10.2 mm

OPERATING TEMPERATURE

-40 TO +85°C

OPERATING VOLTAGE

8 ~ 14 vdc

RATED VOLTAGE

12 vdc

RESONANT FREQUENCY

1000 ~ 1500 Hz

ROHS COMPLAINT

YES

SOUND LEVEL OUTPUT

85dB @ 10 cm

TERMINAL TYPE

2 Pins

1337 Lincoln Avenue Suite 5 Holbrook, NY 11741 , Telephone: (631) 952 - 9595, Fax: