



**International
Components
Corporation**

1337 Lincoln Avenue

Suite 5

Holbrook, NY 11741

Ph: (631) 952 - 9595 Fax: None

E-mail: oemsales@icc107.com

SHIELDED LOW LEAKAGE OVAL SPEAKER

Contact Us



Product: SHIELDED LOW LEAKAGE OVAL SPEAKER

Description: These Speakers Are Available, On A Special Order Basis, In 4, 16, 32, 45 And 100 Ohms.

Part Number: S11X16VNS

SPECIFICATIONS

FRAME DEPTH	11.5 mm
FRAME DIAMETER	28.5 x 40.0 mm
FREQUENCY RESPONSE	Fo ~ 20000
MATERIAL CONE/FRAME	PAPER / ABS
MEAN VALUE AT	0.6, 0.8, 1.0, 1.2KHz
MEASURED AT	1.0 W @ 0.5M
OUTPUT SOUND PRESSURE LEVEL (S.P.L)	82 ± 3 dB
RATED POWER WATTS Nom/Max	1.00 / 2.00
RESONANT FREQUENCY HZ WITOUT BAFFLE	390 ± 20%
ROHS COMPLAINT	YES
VOICE COIL IMPEDANCE	8 ± 15% @ 1.5KHz

1337 Lincoln Avenue Suite 5 Holbrook, NY 11741 , Telephone: (631) 952 - 9595, Fax:None